







T3 Patroller

Electric Stand-up Vehicle

T3 Motion, Inc.

970 Challenger Street, Brea, CA 92821 U.S.A. (714) 255-0200 • www.t3motion.com • sales@t3motion.com







T3 Patroller ESV

Product Specifications

| Description | Specification |
|---|---------------------------------------|
| | |
| Battery | Lithium (up to 25 mile range) |
| Brakes | Twin Rear Hydraulic |
| Clearance | 5 inches |
| Display | Battery meter/odometer/speed |
| Drive System | Front Wheel Drive, 10:1 ratio |
| Front Tire, Pneumatic (inflate to 25 psi) | 15 x 6 4-Ply |
| Front Wheel Rim | 6 x 5 |
| Motor | 1 HP |
| Maximum Speed | Up to 16 mph (Program 5/8/10/12) |
| Maximum High Operating Temperature | +122.0 °F |
| Maximum High Storage Temperature | +158.0 °F |
| Maximum Low Operating Temperature | -50.0 °F |
| Maximum Low Storage Temperature | -68.0 °F |
| Maximum Payload (Rider and Cargo) | 450.0 pounds |
| Maximum Rear Track | 29.5 inches |
| Maximum Vehicle Gross Weight | 750.0 pounds |
| Maximum Width | 34.6/37.5/*39.5 inches (*Elite model) |
| Overall Height @ Headset | 57.0 inches |
| Overall Length | 55.0 inches |
| Platform Height | 9 inches |
| Rear Tires, Pneumatic (inflate to 25 psi) | 120/60-17 |
| Rear Wheel Rim | 17 x 3.5 |
| Turn Radius | <zero-degree< td=""></zero-degree<> |
| Vehicle Curb Weight | 300.0 pounds |
| Vehicle Dry Weight (w/o Power Modules) | 260.0 pounds |
| Width @ Handlebar | 31.0 inches |

»The T3 Patroller ESV is a stable, three-wheeled platform designed to handle both exterior and interior patrol environments and features reversible rear rims for narrow (34.6") and wide (37.5") stance configurations. Options include 100W P.A., On-board Cameras, ALPR, and External Racks.

»The T3 Patroller comes in three models—Full-suspension (Elite), Front suspension (Premium), and Rigid chassis (Standard). Reverse is standard on the Elite and optional on the Premium + Standard.

»The T3 Patroller is multi-shift capable through the revolutionary T3 Motion interchangeable battery system, allowing for one T3 Patroller to operate 24/7 by just "hot-swapping" the batteries.

T3 Motion, Inc., All rights reserved. The T3 Shield is a registered trademark of T3 Motion, Inc. All other trademarks and logos are proprietary of their respective owners. Specifications are subject to change without notice. © 2016